

General Drive

G100



General

Product code		6040000200
Product description		LSLV0008G100-2EONN
Enclosure Rating		IP20, UL Type 1 (Optional)
Input Rating (3-Phase)	Supply Voltage [VAC]	200~240 VAC
	Rated Current [HD/Heavy Duty]	4.9 A
	Rated Current [ND/Normal Duty]	6.3 A
	Supply Frequency [Hz]	50~60 Hz
Input Rating (1-Phase)	Supply Voltage (VAC)	240 VAC
	Rated Current (HD)	4.9 A
	Rated Current (ND)	6.3 A
	Supply Frequency (Hz)	50~60 Hz
Output Rating (3-Phase Input)	Output Voltage (VAC)	200~240 VAC
	Motor Power HP (HD)	1.0 hp
	Motor Power HP (ND)	2.0 hp
	Motor Power kW (HD)	0.75 kW
	Motor Power kW (ND)	1.5 kW
	Output Current (HD)	5.0 A
	Output Current (ND)	6.0 A
	Rated Capacity (HD)	1.9 kVA
	Rated Capacity (ND)	2.3 kVA

	Output Frequency [Hz]	0~400 Hz
Output Rating (1-Phase Input)	Output Voltage [VAC]	-
	Motor Power HP [HD]	0.5 hp
	Motor Power HP [ND]	0.75 hp
	Output Current [HD]	2.8 A
	Output Current [ND]	3.6 A
	Rated Capacity [HD]	-
	Rated Capacity [ND]	-
	Output Frequency [Hz]	-

General

Short Circuit Rating		100kA (IEC 60439-1)
Overload Capacity	HD	150% for 1min
	ND	120% for 1min
Control Method		V/F control, Slip compensation, Sensorless vector
Input Terminals		5 Points
Output Terminals	Relay Output	2 Points
	Open Collector Output	-
EMC Filter		-
DC Reactor		-
Communication	Built-in	Modbus RTU, LS INV 485
	Option	RAPIDnet+, EtherNet/IP, Modbus TCP, Profibus-DP, CAN open
Option Card		Remote Cable, Remote Keypad, Conduit

Environment

Ambient Temperature	HD	-10~50°C (14~122°F)
	ND	-10~40°C (14~104°F)
Storage Temperature		-20~65°C (-4~149°F)
Humidity		Relative humidity of 95% RH or below (without dew formation)
Vibration		9.8m/sec ² (1.0G) or below

Altitude	1,000m above sea level (From 1,000m or more, voltage/ output current derating by 1% for every 100m elevation; up to 4,000m)
Certification	KC, CE, UL, cUL

Dimensions

Frame	A	
W x H x D	mm	86.2 x 164 x 131.5
	inch	3.39 x 6.46 x 5.18

Drawing

