

High Performance Drive

iS7



General

| | | |
|-------------------------------|--------------------------------|---------------|
| Product code | | 6121007200 |
| Product description | | SV0015iS7-4SP |
| Enclosure Rating | | IP54 |
| Input Rating (3-Phase) | Supply Voltage [VAC] | 380~480 VAC |
| | Rated Current [HD/Heavy Duty] | 3.6 A |
| | Rated Current [ND/Normal Duty] | 5.7 A |
| | Supply Frequency [Hz] | 50~60 Hz |
| Input Rating (1-Phase) | Supply Voltage (VAC) | 480 VAC |
| | Rated Current (HD) | 3.6 A |
| | Rated Current (ND) | 5.7 A |
| | Supply Frequency (Hz) | 60 Hz |
| Output Rating (3-Phase Input) | Output Voltage (VAC) | 380~480 VAC |
| | Motor Power HP (HD) | 2 hp |
| | Motor Power HP (ND) | 3 hp |
| | Motor Power kW (HD) | 1.5 kW |
| | Motor Power kW (ND) | 2.2 kW |
| | Output Current (HD) | 4 A |
| | Output Current (ND) | 6 A |
| | Rated Capacity (HD) | 3.0 kVA |
| | Rated Capacity (ND) | - |

| | | |
|-------------------------------|-----------------------|----------|
| | Output Frequency [Hz] | 0~400 Hz |
| Output Rating (1-Phase Input) | Output Voltage [VAC] | - |
| | Motor Power HP [HD] | 0.75 hp |
| | Motor Power HP [ND] | 1 hp |
| | Output Current [HD] | 2.1 A |
| | Output Current [ND] | 3.2 A |
| | Rated Capacity [HD] | - |
| | Rated Capacity [ND] | - |
| | Output Frequency [Hz] | - |

General

| | | |
|----------------------|-----------------------|--|
| Short Circuit Rating | | 100kA (IEC 60439-1) |
| Overload Capacity | HD | 150% for 1min |
| | ND | 110% for 1min |
| Control Method | | V/F, V/F PG, Slip compensation, Sensorless, Vector control |
| Input Terminals | | 8 Points |
| Output Terminals | Relay Output | 2 Points |
| | Open Collector Output | 1 Point |
| EMC Filter | | - |
| DC Reactor | | - |
| Communication | Built-in | Modbus RTU, LS INV 485 |
| | Option | RAPIDnet+, EtherNet/IP, Modbus TCP, CANopen, Profibus-DP, PROFINET, CC-LINK, CC-LINK IE |
| Option Card | | PLC, Extension I/O, Safety(Built-In option), Synchronous, Position, Binary input, Encoder, 24V Encoder, Remote cable(2/3m) |

Environment

| | | |
|---------------------|----|---------------------|
| Ambient Temperature | HD | -10~50°C (14~122°F) |
| | ND | -10~40°C (14~104°F) |
| Storage Temperature | | -20~65°C (-4~149°F) |

| | |
|---------------|--|
| Humidity | Relative humidity of 95% RH or below (without dew formation) |
| Vibration | 9.8m/sec ² (1.0G) or below |
| Altitude | 1,000m above sea level (From 1,000m or more, voltage/output current derating by 1% for every 100m elevation; up to 4,000m) |
| Certification | KC, CE, UL, cUL, Safety, C-Tick ABS, BV, DNV, KR |

Dimensions

| | | |
|-----------|------|---------------------|
| Frame | A | |
| W x H x D | mm | 204.2 x 419 x 208 |
| | inch | 8.04 x 16.50 x 8.19 |

Drawing

