

## High Performance Drive

### iS7



#### General

Product code		6121000300
Product description		SV0022iS7-4NOFD
Enclosure Rating		IP20
Input Rating (3-Phase)	Supply Voltage [VAC]	380~480 VAC
	Rated Current [HD/Heavy Duty]	5.5 A
	Rated Current [ND/Normal Duty]	7.7 A
	Supply Frequency [Hz]	50~60 Hz
Input Rating (1-Phase)	Supply Voltage (VAC)	480 VAC
	Rated Current (HD)	5.5 A
	Rated Current (ND)	7.7 A
	Supply Frequency (Hz)	60 Hz
Output Rating (3-Phase Input)	Output Voltage (VAC)	380~480 VAC
	Motor Power HP (HD)	3 hp
	Motor Power HP (ND)	5 hp
	Motor Power kW (HD)	2.2 kW
	Motor Power kW (ND)	3.7 kW
	Output Current (HD)	6 A
	Output Current (ND)	8 A
	Rated Capacity (HD)	4.5 kVA
	Rated Capacity (ND)	-

	Output Frequency [Hz]	0~400 Hz
Output Rating (1-Phase Input)	Output Voltage [VAC]	-
	Motor Power HP [HD]	1 hp
	Motor Power HP [ND]	2 hp
	Output Current [HD]	2.8 A
	Output Current [ND]	4.1 A
	Rated Capacity [HD]	-
	Rated Capacity [ND]	-
	Output Frequency [Hz]	-

### General

Short Circuit Rating		100kA (IEC 60439-1)
Overload Capacity	HD	150% for 1min
	ND	110% for 1min
Control Method		V/F, V/F PG, Slip compensation, Sensorless, Vector control
Input Terminals		8 Points
Output Terminals	Relay Output	2 Points
	Open Collector Output	1 Point
EMC Filter		Built-in
DC Reactor		Built-in
Communication	Built-in	Modbus RTU, LS INV 485
	Option	RAPiEnet+, EtherNet/IP, Modbus TCP, CANopen, Profibus-DP, PROFINET, CC-LINK, CC-LINK IE
Option Card		PLC, Extension I/O, Safety(Built-In option), Synchronous, Position, Binary input, Encoder, 24V Encoder, Remote cable(2/3m)

### Environment

Ambient Temperature	HD	-10~50°C (14~122°F)
	ND	-10~40°C (14~104°F)
Storage Temperature		-20~65°C (-4~149°F)

