

## High Performance Drive

### iS7



#### General

Product code		6120005000
Product description		SV0220iS7-2SP
Enclosure Rating		IP54
Input Rating (3-Phase)	Supply Voltage [VAC]	200~240 VAC
	Rated Current [HD/Heavy Duty]	85.3 A
	Rated Current [ND/Normal Duty]	116.1 A
	Supply Frequency [Hz]	50~60 Hz
Input Rating (1-Phase)	Supply Voltage (VAC)	240 VAC
	Rated Current (HD)	85.3 A
	Rated Current (ND)	116.1 A
	Supply Frequency (Hz)	60 Hz
Output Rating (3-Phase Input)	Output Voltage (VAC)	200~230 VAC
	Motor Power HP (HD)	30 hp
	Motor Power HP (ND)	40 hp
	Motor Power kW (HD)	22 kW
	Motor Power kW (ND)	30 kW
	Output Current (HD)	88 A
	Output Current (ND)	124 A
	Rated Capacity (HD)	33.5 kVA
Rated Capacity (ND)	-	

	Output Frequency [Hz]	0~400 Hz
Output Rating (1-Phase Input)	Output Voltage [VAC]	-
	Motor Power HP [HD]	15 hp
	Motor Power HP [ND]	20 hp
	Output Current [HD]	45.0 A
	Output Current [ND]	64.0 A
	Rated Capacity [HD]	-
	Rated Capacity [ND]	-
	Output Frequency [Hz]	-

### General

Short Circuit Rating		100kA (IEC 60439-1)
Overload Capacity	HD	150% for 1min
	ND	110% for 1min
Control Method		V/F, V/F PG, Slip compensation, Sensorless, Vector control
Input Terminals		8 Points
Output Terminals	Relay Output	2 Points
	Open Collector Output	1 Point
EMC Filter		-
DC Reactor		-
Communication	Built-in	Modbus RTU, LS INV 485
	Option	RAPiEnet+, EtherNet/IP, Modbus TCP, CANopen, Profibus-DP, PROFINET, CC-LINK, CC-LINK IE
Option Card		PLC, Extension I/O, Synchronous, Position, Binary input, Encoder, 24V Encoder, Remote cable(2/3m)

### Environment

Ambient Temperature	HD	-10~50°C (14~122°F)
	ND	-10~40°C (14~104°F)
Storage Temperature		-20~65°C (-4~149°F)
Humidity		Relative humidity of 95% RH or below (without dew formation)

Vibration	9.8m/sec <sup>2</sup> (1.0G) or below
Altitude	1,000m above sea level (From 1,000m or more, voltage/ output current derating by 1% for every 100m elevation; up to 4,000m)
Certification	KC, CE, UL, cUL, Safety, C-Tick ABS, BV, DNV, KR

### Dimensions

Frame	D	
W x H x D	mm	343.2 x 750.8 x 315.5
	inch	13.51 x 29.56 x 12.42

### Drawing

