

High Performance Drive

iS7



General

Product code		6120000700
Product description		SV0110iS7-2NOFD
Enclosure Rating		IP20
Input Rating (3-Phase)	Supply Voltage [VAC]	200~240 VAC
	Rated Current [HD/Heavy Duty]	44.3 A
	Rated Current [ND/Normal Duty]	54.7 A
	Supply Frequency [Hz]	50~60 Hz
Input Rating (1-Phase)	Supply Voltage (VAC)	240 VAC
	Rated Current (HD)	44.3 A
	Rated Current (ND)	54.7 A
	Supply Frequency (Hz)	60 Hz
Output Rating (3-Phase Input)	Output Voltage (VAC)	200~230 VAC
	Motor Power HP (HD)	15 hp
	Motor Power HP (ND)	20 hp
	Motor Power kW (HD)	11 kW
	Motor Power kW (ND)	15 kW
	Output Current (HD)	46 A
	Output Current (ND)	60 A
	Rated Capacity (HD)	17.5 kVA
	Rated Capacity (ND)	-

	Output Frequency (Hz)	0~400 Hz
Output Rating (1-Phase Input)	Output Voltage [VAC]	-
	Motor Power HP [HD]	7.5 hp
	Motor Power HP [ND]	10 hp
	Output Current [HD]	24.0 A
	Output Current [ND]	31.0 A
	Rated Capacity [HD]	-
	Rated Capacity [ND]	-
	Output Frequency [Hz]	-

General

Short Circuit Rating		100kA (IEC 60439-1)
Overload Capacity	HD	150% for 1min
	ND	110% for 1min
Control Method		V/F, V/F PG, Slip compensation, Sensorless, Vector control
Input Terminals		8 Points
Output Terminals	Relay Output	2 Points
	Open Collector Output	1 Point
EMC Filter		Built-in
DC Reactor		Built-in
Communication	Built-in	Modbus RTU, LS INV 485
	Option	RAPiEnet+, EtherNet/IP, Modbus TCP, CANopen, Profibus-DP, PROFINET, CC-LINK, CC-LINK IE
Option Card		PLC, Extension I/O, Synchronous, Position, Binary input, Encoder, 24V Encoder, Remote cable(2/3m)

Environment

Ambient Temperature	HD	-10~50°C (14~122°F)
	ND	-10~40°C (14~104°F)
Storage Temperature		-20~65°C (-4~149°F)
Humidity		Relative humidity of 95% RH or below (without dew formation)

Vibration	9.8m/sec ² (1.0G) or below
Altitude	1,000m above sea level (From 1,000m or more, voltage/ output current derating by 1% for every 100m elevation; up to 4,000m)
Certification	KC, CE, UL, cUL, Safety, C-Tick ABS, BV, DNV, KR

Dimensions

Frame		C
W x H x D	mm	250 x 385 x 284
	inch	9.84 x 15.16 x 11.18

Drawing

